

PS-12750 12 Volt 75.0 AH Rechargeable Sealed Lead Acid Battery



We've Got The Power.™




Features

- Absorbent Glass Mat (AGM) technology for superior performance
- Valve regulated, spill proof construction allows safe operation in any position
- Power/volume ratio yielding unrivaled energy density
- Rugged impact resistant ABS case and cover (UL94-HB)
- Integrated ABS carrying handles for ease of movement
- Approved for transport by air. D.O.T., I.A.T.A., F.A.A. and C.A.B. certified
- U.L. recognized under file number MH 20845

Terminals

(mm)


- U: Universal terminals: Heavy-duty posts with 'nut & bolt' fasteners



Performance Specifications

| | |
|---|--|
| Nominal Voltage | 12 volts (6 cells) |
| Nominal Capacity | |
| 20-hr. (3.75A to 10.50 volts) | 75.0 AH |
| 10-hr. (7.2A to 10.50 volts) | 72.0 AH |
| 5-hr. (13.6A to 10.20 volts) | 68.0 AH |
| 1-hr. (47A to 9.00 volts) | 47.0 AH |
| 15-min. (160A to 9.00 volts) | 40.0 AH |
| Approximate Weight | 50.60 lbs. (22.95 kg) |
| Energy Density (20-hr. rate) | 1.63 W-h/in ³ (99.61 W-h/l) |
| Specific Energy (20-hr. rate) | 17.79 W-h/lb (39.21 W-h/kg) |
| Internal Resistance (approx.) | 6 milliohms |
| Max Discharge Current (7 Min.) | 225.0 amperes |
| Max Short-Duration Discharge Current (10 Sec.) | 560.0 amperes |
| Shelf Life (% of nominal capacity at 68°F (20°C)) | |
| 1 Month | 97% |
| 3 Months | 91% |
| 6 Months | 83% |
| Operating Temperature Range | |
| Charge | -4°F (-20°C) to 122°F (50°C) |
| Discharge | -40°F (-40°C) to 140°F (60°C) |
| Case | ABS Plastic |
| Power-Sonic Chargers | PSC-1210000A-C |

Physical Dimensions: in (mm)




L: 10.25 (260) W: 6.60 (168) H: 8.15 (207) HT: 8.98 (228)

Tolerances are +/- 0.04 in. (+/- 1mm) and +/- 0.08 in. (+/- 2mm) for height dimensions. All data subject to change without notice.


Constant Power Discharge Ratings

| MODEL | FINAL VOLTAGE | WATTS PER CELL @ 25° C | | | | | | |
|-----------------|---------------|------------------------|--------|--------|--------|--------|--------|--------|
| | | 5 MIN | 10 MIN | 15 MIN | 20 MIN | 30 MIN | 45 MIN | 60 MIN |
| PS-12750 | 1.75 | 480 | 339 | 270 | 220 | 168 | 126 | 102 |
| | 1.70 | 509 | 356 | 278 | 231 | 171 | 128 | 103 |
| | 1.67 | 518 | 360 | 282 | 233 | 173 | 130 | 106 |

Discharge Time vs. Discharge Current



Discharge Characteristics




Charging

Cycle Applications: Limit initial current to 22.5A. Charge until battery voltage (under charge) reaches 14.4 to 14.7 volts at 68°F (20°C). Hold at 14.4 to 14.7 volts until current drops to under 750mA. Battery is fully charged under these conditions, and charger should be disconnected or switched to “float” voltage.

“Float” or “Stand-By” Service: Hold battery across constant voltage source of 13.5 to 13.8 volts continuously. When held at this voltage, the battery will seek its own current level and maintain itself in a fully charged condition.

Note: Due to the self-discharge characteristics of this type of battery, it is imperative that they be charged within 6 months of storage, otherwise permanent loss of capacity might occur as a result of sulfation.

Shelf Life & Storage



Chargers

Power-Sonic offers a wide range of chargers suitable for batteries up to 100AH. Please refer to the Charger Selection Guide in our specification sheets for “C-Series Switch Mode Chargers” and “Transformer Type A and F Series”. Please contact our Technical department for advice if you have difficulty in locating suitable models.

Further Information

Please refer to our website www.power-sonic.com for a complete range of useful downloads, such as product catalogs, material safety data sheets (MSDS), ISO certification, etc..

Contact Information

www.power-sonic.com

DOMESTIC SALES

Tel: +1-619-661-2020
 Fax: +1-619-661-3650
 national-sales@power-sonic.com

CUSTOMER SERVICE

Tel: +1-619-661-2030
 Fax: +1-619-661-3648
 customer-service@power-sonic.com

TECHNICAL SUPPORT

Tel: +1-619-661-2020
 Fax: +1-619-661-3648
 support@power-sonic.com

INTERNATIONAL SALES

Tel: +1-650-364-5001
 Fax: +1-650-366-3662
 battery@power-sonic.com